

EMBEDDED PUBLIC EMERGENCY TELEPHONE PT-M-MT2

Live broadcasting ,one push to call,waterproof and dustproof

Solid waterproof structure, slogan Logo and color support be customized silk screen, eye-catching high visibility color coating.



Features

- Size:300*220*50mm
- Weight: 4KG
- Material: cold rolled steel plate
- Installation method: wall mounted and embedded installation
- Call mode: hands free
- Button: 304 stainless steel,IP67 weather protection
- Auto answer time:1-30 seconds (can be adjusted)
- Calling limited time: 1-9 minutes (can be adjusted)
- Phone port: RJ11
- Power supply: 9V AC or no need power supply also will be working
- Broadcasting power: 1W
- Broadcasting distance: 20 square

Applications

- Tunnel, steel workshop, mines,
- Bridge, power plant rooms, highway toll stations

Specifaction

Power supply mode	telephone line for power supply or DC9V
DTMF dialing parameters	
Low frequency group frequency	697.770.852.941HZ
High frequency group frequency	1209.1336.1477HZ
Frequency deviation	≤ 1.5%;
Low frequency group level	-9 + 3dB;



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution
FengHuang first industry park,fuyong town,ShenZhen
Tel:86-075589487736 Fax:86-075533671258

High frequency group level	-7 + 3dB
Level difference between the high and low level frequency	2 + 1dB
Harmonic total distortion at least low 20dB than the fundamental level	
Ringing tone decibel	70dB
Speaker decibel	90dB (external power supply)
Phone impedance	600 Ω
Memory	EEPROM (power off without loss data)
Interface	RJ11 or 2P terminal
Parameter setting	by keyboard DTMF dial set

Related products



Drawings



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution
 FengHuang first industry park, fuyong town, ShenZhen
 Tel:86-075589487736 Fax:86-075533671258