

FLUSH MOUNT EMERGENCY TELEPHONE PT-S-MT2

304 stain less steel housing, vandal resistant, one button auto dialing, waterproof



Features

- *size:110*185*32mm
- *weight: 1.0KG
- *Flush-mounted
- *Waterproof and dustproof, anti-vandal
- *Stainless steel housing and call button
- *Waterproof grade: IP65-IP67
- *Can prestore one groups of number, starting up then make emergency call.
- *Phone line for power supply, no external power supply
- *Microphone sensitivity can adjusted
- *Build in speakerphone calls in with very loud speaking

Usage condition

Temperature	-10℃~+50℃	Relative humidity	45%-75%
Atmospheric pressure	86~106Kpa	Environmental noise	less than 90dB
Usage condition	24-60V PBX telephone	Ringling Level	70-90V
Busy tone	300~450HZ, interval between 300-500ms		
Telephone line current	>=20mA		

Telephone parameters

Power supply mode	telephone line for power supply or DC9V
DTMF dialing parameters	
Low frequency group frequency	697.770.852.941HZ
High frequency group frequency	1209.1336.1477HZ
Frequency deviation	≤ 1.5%;
Low frequency group level	-9 + 3dB;
High frequency group level	-7 + 3dB



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution
 FengHuang first industry park, fuyong town, ShenZhen
 Tel:86-075589487736 Fax:86-075533671258

Level difference between the high and low level frequency	2 + 1dB
Harmonic total distortion at least low 20dB than the fundamental level	
Ringing tone decibel	70dB
Speaker decibel	90dB (external power supply)
Phone impedance	600 Ω
Memory	EEPROM (power off without loss data)
Interface	RJ11 or 2P terminal
Parameter setting	by keyboard DTMF dial set

Related products



Drawings



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution
 FengHuang first industry park,fuyong town,ShenZhen
 Tel:86-075589487736 Fax:86-075533671258