

OUTDOOR EMERGENCY TELEPHONE PT-M-WMT2

Wireless GSM ,weatherproof, vandal resistant, simple to maintain



Features

- Size: 2200*450*450mm
- Weight: 50 KG
- Material: cold rolled steel plate
- Call mode: telephone receiver
- Network frequency: GSM850/900/1800/1900
- Programming remotely via SMS
- Anti interference design, strong anti-interference ability
- Armoured cord handset
- Waterproof grade IP66
- Emergency button: 304 stainless steel
- SIM card: standard card
- Speaking distance: 30-100cm
- Solar powered
- VoIP GSM and analog can be supported

Applications

- Scenic area
- Highway
- Roadside
- Public square
- Outside building
- Transit facilities

Specifications

Frequency Band	◆ 850/ 900/ 1800/ 1900MHz
Sensitivity	◆ GSM850: -109dBm ◆ GSM900: -109dBm ◆ DCS1800: -109dBm ◆ PCS1900: -109dBm
Consumption	◆ 1.3mA @DRX=5 ◆ 1.2mA @DRX=9
Transmit power	◆ Class 4 (2W @850/ 900MHz) ◆ Class 1 (1W @1800/ 1900MHz)
Microphone sensitivity	◆ -52dB
Audio amplifier	◆ 2W
SIM card interface	◆ Standard card 1.8,3.3V



Specialized in emergency telephone solution

Speech codec modes	<ul style="list-style-type: none"> ◆ Half Rate (HR) ◆ Full Rate (FR) ◆ Enhanced Full Rate (EFR) ◆ Adaptive Multi-Rate (AMR) Echo Arithmetic: ◆ Echo Cancellation ◆ Echo Suppression ◆ Noise Reduction
Maximum storage number	◆ 6 numbers
Function	<ul style="list-style-type: none"> ◆ Support switch signal output(3.3V) ◆ support alarm light output(12V ,1A)
Supply voltage	◆ 9V~12V, 12V Typ.
Working temperature	◆ -40°C ~ +85°C

Drawings



Specialized in emergency telephone solution