

## TALKBACK CALL STATION WITH RAIN COVER PT-WMT2

Stainless steel housing, vandal resistant, one button auto dialing, waterproof



### Features

- \*size:230\*160\*80mm
- \*weight: 2.0KG
- \*Wall mounted or embedded installation
- \*Waterproof and dustproof, anti-vandal
- \*Stainless steel housing and call button
- \*Waterproof grade: IP65-IP67
- \*Can prestore one groups of number, starting up then make emergency call.
- \*Phone line for power supply, no external power supply
- \*Microphone sensitivity can adjusted
- \*Build in speakerphone calls in with very loud speaking
- \*Eye -catching coating

### Usage condition

Temperature	-10℃~+50℃	Relative humidity	45%-75%
Atmospheric pressure	86~106Kpa	Environmental noise	less than 90dB
Usage condition	24-60V PBX telephone	Ringin Level	70-90V
Busy tone	300~450HZ, interval between 300-500ms		
Telephone line current	≥20mA		

### Telephone parameters

Power supply mode	telephone line for power supply or DC9V
DTMF dialing parameters	
Low frequency group frequency	697.770.852.941HZ
High frequency group frequency	1209.1336.1477HZ
Frequency deviation	≤ 1.5%;



PPST Technology Co.,LTD  
[www.waterproof-phone.com](http://www.waterproof-phone.com)

*Specialized in emergency telephone solution*  
 FengHuang first industry park,fuyong town,ShenZhen  
 Tel:86-075589487736 Fax:86-075533671258

Low frequency group level	-9 + 3dB;
High frequency group level	-7 + 3dB
Level difference between the high and low level frequency	2 + 1dB
Harmonic total distortion at least low 20dB than the fundamental level	
Ringing tone decibel	70dB
Speaker decibel	90dB (external power supply)
Phone impedance	600 Ω
Memory	EEPROM (power off without loss data)
Interface	RJ11 or 2P terminal
Parameter setting	by keyboard DTMF dial set

## Related products



## Drawings



PPST Technology Co.,LTD  
[www.waterproof-phone.com](http://www.waterproof-phone.com)

*Specialized in emergency telephone solution*  
 FengHuang first industry park,fuyong town,ShenZhen  
 Tel:86-075589487736 Fax:86-075533671258