

WALL MOUNTED EMERGENCY CALL BOX PT-M-MT4

Cold rolled stainless steel housing, waterproof and dustproof



Features

- Size:300*220*50mm
- Material: cold rolled steel plate
- Installation method: embedded installation
- Call mode: hands free
- Button: 304 stainless steel,IP67 weather protection
- Auto answer time:1-30 seconds (can be adjusted)
- Calling barring time: 1-9 minutes/can be turn off
- Phone port: RJ11
- Power supply: DC9V or no power supply also can be working
- Broadcasting power: 1W
- Broadcasting distance: 20 square (indoor)

Applications

- Tunnel
- Bridge
- Highway toll station

Specification

Power supply mode	telephone line for power supply or DC9V
DTMF dialing parameters	
Low frequency group frequency	697.770.852.941HZ
High frequency group frequency	1209.1336.1477HZ
Frequency deviation	≤ 1.5%;
Low frequency group level	-9 + 3dB;
High frequency group level	-7 + 3dB
Level difference between the high and low level frequency	2 + 1dB
Harmonic total distortion at least low 20dB than the fundamental level	



Specialized in emergency telephone solution

Ringing tone decibel	70dB
Speaker decibel	90dB (external power supply)
Phone impedance	600 Ω
Memory	EEPROM (power off without loss data)
Interface	RJ11 or 2P terminal
Parameter setting	by keyboard DTMF dial set

Related products



Drawings



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution

FengHuang first industry park,fuyong town,ShenZhen
 Tel:86-075589487736 Fax:86-075533671258