

ELEVATOR TELEPHONE WITH TWO BUTTON PT-S-MT6

Aluminum alloy die casting housing, vandal resistant, one button auto dialing, waterproof

PT-S-MT6 the elevator specialized telephone is suitable for the community property, the elevator monitoring, the elevator intercom and so on. Simple operation, one button to call, no manually dial design, one group numbers can be prestored, automatic dial when start. Convenient installation, no need to change the elevator's internal structure, appearance and the operation method of the original elevator, then realize the concentrated monitoring and management of the elevators



Features

- *size:110*185*32mm
- *weight: 2.0KG
- *Wall-mounted and embedded installation
- *Waterproof and dustproof, anti-vandal
- *Stainless steel housing and call button
- *Can prestore one groups of number, starting up then make emergency call
- *When callings in, auto answer, self stop if the other side hang up.
- *Phone line for power supply, no external power supply
- *Microphone sensitivity can adjusted
- *Build in speakerphone covered with steel mesh, puncture resistant

Usage condition

Temperature	-10℃~+50℃	Relative humidity	45%-75%
Atmospheric pressure	86~106Kpa	Environmental noise	less than 90dB
Usage condition	24-60V PBX telephone	Ringling Level	70-90V
Busy tone	300~450HZ, interval between 300-500ms		
Telephone line current	≥20mA		

Telephone parameters

Power supply mode	telephone line for power supply or DC9V
-------------------	---



PPST Technology Co.,LTD
www.waterproof-phone.com


Specialized in emergency telephone solution
 FengHuang first industry park, fuyong town, ShenZhen
 Tel:86-075589487736 Fax:86-075533671258

DTMF dialing parameters	
Low frequency group frequency	697.770.852.941HZ
High frequency group frequency	1209.1336.1477HZ
Frequency deviation	≤ 1.5%;
Low frequency group level	-9 + 3dB;
High frequency group level	-7 + 3dB
Level difference between the high and low level frequency	2 + 1dB
Harmonic total distortion at least low 20dB than the fundamental level	
Ringing tone decibel	70dB
Speaker decibel	90dB (external power supply)
Phone impedance	600 Ω
Memory	EEPROM (power off without loss data)
Interface	RJ11 or 2P terminal
Parameter setting	by keyboard DTMF dial set

Related products



Drawings



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution
 FengHuang first industry park, fuyong town, ShenZhen
 Tel:86-075589487736 Fax:86-075533671258