

GSM SOS CALL STATION PT-M-WMT2

GSM wireless, waterproof and dustproof simple for maintain



Features

- Size: 300*220*50MM
- Weight: 3.0KG
- Material: stainless steel
- Installation method: wall mounted or embedded
- Call mode: Handset
- Waterproof grade IP54
- Anti interference design, strong anti-interference ability
- SIM card: standard card
- Telephone line powered, no need external power supply
- Simple to maintain
- Programmable remotely via SMS

Applications

metro stations, railway platform, highway side, hotels, parking lots, steel Plants, chemical plants, power plants and related heavy duty industria

Specifications

Frequency Band	<ul style="list-style-type: none"> ◆ 850/ 900/ 1800/ 1900MHz
Sensitivity	<ul style="list-style-type: none"> ◆ GSM850: -109dBm ◆ GSM900: -109dBm ◆ DCS1800: -109dBm ◆ PCS1900: -109dBm
Consumption	<ul style="list-style-type: none"> ◆ 1.3mA @DRX=5 ◆ 1.2mA @DRX=9
Transmit power	<ul style="list-style-type: none"> ◆ Class 4 (2W @850/ 900MHz) ◆ Class 1 (1W @1800/ 1900MHz)
Microphone sensitivity	<ul style="list-style-type: none"> ◆ -52dB
Audio amplifier	<ul style="list-style-type: none"> ◆ 2W
SIM card interface	<ul style="list-style-type: none"> ◆ Standard card 1.8,3.3V



Specialized in emergency telephone solution

Speech codec modes	<ul style="list-style-type: none"> ◆ Half Rate (HR) ◆ Full Rate (FR) ◆ Enhanced Full Rate (EFR) ◆ Adaptive Multi-Rate (AMR) Echo Arithmetic: ◆ Echo Cancellation ◆ Echo Suppression ◆ Noise Reduction
Maximum storage number	◆ 6 numbers
Function	<ul style="list-style-type: none"> ◆ Support switch signal output(3.3V) ◆ support alarm light output(12V ,1A)
Supply voltage	◆ 9V~12V, 12V Typ.
Working temperature	◆ -40°C ~ +85°C

Related products



Drawings



Specialized in emergency telephone solution

PPST Technology Co.,LTD
www.waterproof-phone.com

FengHuang first industry park,fuyong town,ShenZhen
 Tel:86-075589487736 Fax:86-075533671258