

INDUSTRIAL WATERPROOF TELEPHONE PT-IPFS2

Weatherproof, SMC composite enclosure



Features

- Size: 350*270*127 (mm)
- Weight: 7.5KG
- SMC composite enclosure, impact resistant
- Excellent waterproof and dustproof
- Silica gel keypad, M1 M2 for speed dial, HF for handsfree model
- Waterproof grade IP67
- Standard VoIP protocol
- powered by POE or external power supply
- Configuration and firmware upgrades through Web GUI

Applications

- Roadside
- Mining plant
- Chemical plant
- Steel Plant
- Power plant
- Heavy duty industrial

Specifications

Network Protocol	<ul style="list-style-type: none"> ◆ SIP v1 (RFC2543), v2(RFC3261) ◆ IP/TCP/UDP/RTP/RTCP ◆ IP/ICMP/ARP/RARP/SNTP ◆ TFTP Client/DHCP Client/ PPPoE Client ◆ Telnet/HTTP Server ◆ DNS Client
Codec	<ul style="list-style-type: none"> ◆ G.711: 64k bit/s (PCM) ◆ G.723.1: 6.3k / 5.3k bit/s ◆ G.726: 16k / 24k / 32k / 40k bit/s (ADPCM) ◆ G.729A: 8k bit/s (CS-ACELP) ◆ G.729B: adds VAD & CNG to G.729
Call	<ul style="list-style-type: none"> ◆ Call Hold Call Waiting Call Forward Caller ID 3-way conference
DTMF Function	<ul style="list-style-type: none"> ◆ In-Band DTMF ◆ Out-of Band DTMF ◆ SIP Info



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution
 FengHuang first industry park, fuyong town, ShenZhen
 Tel:86-075589487736 Fax:86-075533671258

Tone	<ul style="list-style-type: none"> ◆ Ring Tone ◆ Ring Back Tone ◆ Dial Tone ◆ Busy Tone ◆ User Programming Tone
Voice Quality	<ul style="list-style-type: none"> ◆ VAD: Voice activity detection ◆ CNG: Comfortable noise generator ◆ LEC: Line echo canceller ◆ Packet Loss Compensation ◆ Adaptive Jitter Buffer
Phone Function	<ul style="list-style-type: none"> ◆ Volume Adjustment ◆ Speed dial, Phone book ◆ Flash ◆ Speaker Phone
Security	<ul style="list-style-type: none"> ◆ HTTP 1.1 basic/digest authentication for Web setup ◆ MD5 for SIP authentication (RFC2069/ RFC 2617)
Working environment	<ul style="list-style-type: none"> ◆ Ambient temperature:-20-50℃ ◆ Relative humidity: 10-95%
Accessories parameters	<ul style="list-style-type: none"> ◆ Speaker:8Ω 1W ◆ Microphone: sensitivity -50db ◆ Housing: SMC composite material

Related products



Drawing



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution
 FengHuang first industry park,fuyong town,ShenZhen
 Tel:86-075589487736 Fax:86-075533671258