

LOUD SPEAKING WEATHERPROOF TELEPHONEPT-WESP1

Live broadcasting , strong penetrating power of the loudspeaker

This series of industrial broadcasting telephones are fixed the loud speakerphone at the top of the device, and support multi-channel broadcast output, which has powerful broadcast call and call reminder function. The shell is 2mm thick cold rolled steel plate. the structure is solid and the surface conformally coated with outdoor paint



Features

- Size:280*220*160mm
- Weight: 3KG
- Material: cold rolled steel plate
- Installation method: wall mounted or embedded installation
- Call mode: telephone receiver
- Keypad: 16-bit zinc alloy keypad, IP54 weather protection
- Start broadcasting time:1-30 seconds (can be adjusted)
- Calling limited time: when reach limited time ,then hang up automatically
- Phone port: RJ11
- Power supply: 110-220V AC or 24V DC
- Broadcasting power: 30W
- Broadcasting distance: 30-100M
- 25W-30W speakerphone

Applications

- Tunnel, steel workshop, mines,
- Bridge, power plant rooms, highway toll stations
- Coal preparation plant

Specification

Frequency Band	◆ 850/ 900/ 1800/ 1900MHz
Sensitivity	◆ GSM850: -109dBm ◆ GSM900: -109dBm ◆ DCS1800: -109dBm ◆ PCS1900: -109dBm
Consumption	◆ 1.3mA @DRX=5 ◆ 1.2mA @DRX=9
Transmit power	◆ Class 4 (2W @850/ 900MHz) ◆ Class 1 (1W @1800/ 1900MHz)
Microphone sensitivity	◆ -52dB
Audio amplifier	◆ 2W



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution
FengHuang first industry park,fuyong town,ShenZhen
Tel:86-075589487736 Fax:86-075533671258

SIM card interface	<ul style="list-style-type: none"> ◆ Standard card 1.8,3.3V
Speech codec modes	<ul style="list-style-type: none"> ◆ Half Rate (HR) ◆ Full Rate (FR) ◆ Enhanced Full Rate (EFR) ◆ Adaptive Multi-Rate (AMR) <li style="padding-left: 20px;">Echo Arithmetic: ◆ Echo Cancellation ◆ Echo Suppression ◆ Noise Reduction
Maximum storage number	<ul style="list-style-type: none"> ◆ 6 numbers
Function	<ul style="list-style-type: none"> ◆ Support switch signal output(3.3V) ◆ support alarm light output(12V ,1A)
Supply voltage	<ul style="list-style-type: none"> ◆ 9V~12V, 12V Typ.
Working temperature	<ul style="list-style-type: none"> ◆ -40°C ~ +85°C

Related products



Drawing



PPST Technology Co.,LTD
www.waterproof-phone.com

Specialized in emergency telephone solution
 FengHuang first industry park,fuyong town,ShenZhen
 Tel:86-075589487736 Fax:86-075533671258