

WALL MOUNTED EMERGENCY CALL BOX PT-M-MT4

Cold rolled stainless steel housing, waterproof and dustproof



Features

- Size:300*220*50mm
- Material: cold rolled steel plate
- Installation method: embedded installation
- Call mode: hands free
- Button: 304 stainless steel,IP67 weather protection
- Auto answer time:1-30 seconds (can be adjusted)
- Calling barring time: 1-9 minutes/can be turn off
- Phone port: RJ11
- Power supply: DC9V or no power supply also can be working
- Broadcasting power: 1W
- Broadcasting distance: 20 square (indoor)

Applications

- Tunnel
- Bridge
- Highway toll station

Specification

Power supply mode	telephone line for power supply or DC9V
DTMF dialing parameters	
Low frequency group frequency	697.770.852.941HZ
High frequency group frequency	1209.1336.1477HZ
Frequency deviation	≤ 1.5%;
Low frequency group level	-9 + 3dB;
High frequency group level	-7 + 3dB
Level difference between the high and low level frequency	2 + 1dB
Harmonic total distortion at least low 20dB than the fundamental level	



Specialized in emergency telephone solution

Ringing tone decibel	70dB
Speaker decibel	90dB (external power supply)
Phone impedance	600 Ω
Memory	EEPROM (power off without loss data)
Interface	RJ11 or 2P terminal
Parameter setting	by keyboard DTMF dial set

Related products



Drawings



Specialized in emergency telephone solution

PPST Technology Co.,LTD
www.waterproof-phone.com

FengHuang first industry park,fuyong town,ShenZhen
 Tel:86-075589487736 Fax:86-075533671258